



Description

The data logger is a bespoke, site specific logger with various modules and communication options, combined with a power supply, contained within a steel or reinforced GRP IP65 enclosure.

Each logger is customised to specific site requirements and is tested using a logging program, written to suit the sensor types to be used on each project.

We configure all the data logging equipment to suit your individual needs and our technical expertise ensures a tailored solution to read an extensive range of sensors, in a vast range of environments.

Features

- Configured to customer requirements according to sensor, power supply and communication requirements
- Can be configured to read almost any geotechnical or structural monitoring sensor
- Data kept in simple 'ASCII' file for use with web based interfaces such as 'Argus' software, or a spreadsheet

Benefits

- Proven track record on major projects
- Rugged construction
- Low power consumption
- Various communication options available; ADSL, short haul modem, GPRS modem
- Can be powered from mains voltage as well as stand alone wind and solar sources for remote monitoring sites



Comprehensive information about this product and our full range is available at www.soilinstruments.com
 If you would like to speak with someone directly please call +44 (0)1825 765044 or email sales@soilinstruments.com

Operation

Data loggers are supplied with various memory options and further capacity can be added through the addition of a Compact Flash module.

Each logging program is bespoke and written for all types of sensors and projects, drawing from a large software library that allows us to configure a program easily and quickly for any application.

The system can be setup to generate alarms remotely, via email or SMS, or locally using a siren and/or beacon if user defined parameters are exceeded.

The data logger consumes minimal power from either a 12 VDC or mains power source. Power supply options are flexible depending on the site and can include mains, solar cell, and wind generation.

Applications

Data loggers can form part of any automated monitoring system. They are ideally suited for structural and geotechnical monitoring and are used extensively in harsh environments on projects around the world.

Typical applications for datalogged monitoring systems include:

- Dams and bridges
- Tunnels (both during construction and operation)
- Tracks on the railway networks for twist and longitudinal settlement
- Monitoring rock falls
- Any structure adjacent to and affected by construction activities

Communication

A wide variety of communication options are available for the data logger, including:

- Direct link to PC or laptop
- Fibre optic link
- Extended RS485 link (up to 13Km)
- Satellite up link
- Cellular (GSM/GPRS) modem
- Telephone modem
- IP via GPRS modem, i.e. direct to internet
- Dedicated radio communication

Associated products

For details on:

Catalogue Code:

'ARGUS' Monitoring Software

D4

View our full product range on www.soilinstruments.com



THE TECHNICAL RATING FOR THIS PRODUCT:

As the correct installation of any monitoring sensor or system is vital to maximise performance and accuracy, Soil Instruments makes the following recommendations, for the skill level of the installation contractor.

ADDITIONAL SUPPORT

We offer installation and monitoring services to support this system. For more information please email : sales@soilinstruments.com or call : **+44 (0) 1825 765044**

ADVANCED



ADVANCED



The installer is trained and experienced in the installation of this type of instrument or systems, and is ideally a specialist Instrumentation and Monitoring contractor.

INTERMEDIATE



The installer already has previous experience and/or training in the installation of this instrument or system.

BASIC



As a minimum the installer has read and fully comprehends the manual, and if possible has observed these instruments or systems being installed by others.

Specifications

Datalogger

Program Execution Rate	10ms to 30min @ 10ms increments
------------------------	---------------------------------

Analogue Inputs

3 differential (DF) or 6 single-ended (SE) individually configured

Channel expansion provided by AM16/32 and AM25T multiplexers

Ranges and resolution ³	Input Range (mV) ¹	DF Res (µV) ²	Basic Res (µV)
	±5000	667	1333
	±2500	333	667
	±250	33.3	66.7
	±25	3.33	6.7
	±7.5	1	2
	±2.5	0.33	0.67
Accuracy ²	0 to +40°C ±(0.06% of setting + 0.8 mV)	-25 to +50°C ±(0.12% of setting + 0.8 mV)	-55 to +85°C (-XT only) ±(0.18% of setting + 0.8 mV)

Analogue Outputs

2 switched voltage, active only during measurement, one at a time

Ranges and resolution	Voltage outputs programmable between ±2.5 V with 0.67 mV resolution		
Accuracy	0 to +40°C ±(0.06% of setting + 0.8 mV)	-25 to +50°C ±(0.12% of setting + 0.8 mV)	-55 to +85°C (-XT only) ±(0.18% of setting + 0.8 mV)

Resistance Measurements

Measurement types	4- and 6-wire full bridges, 2, 3 and 4 wire half bridges. Precise, dual polarity excitation using any of the 3 switched voltage excitations eliminates dc errors.
Ratio Accuracy	±(0.04% of voltage reading + offset)/V _x

Pulse Counters

Maximum counts per scan	16.7 x 10 ⁶
Digital I/O ports	4 ports software selectable, as binary inputs or control outputs

CR1000 Series Specifications

Program execution rate	10ms to 30min @ 10 ms increments
------------------------	----------------------------------

Analogue Inputs

8 differential (DF) or 16 single-ended (SE) individually configured

Channel expansion provided by AM16/32 and AM25T multiplexers

Ranges and resolution ³	Input Range (mV) ¹	DF Res (µV) ²	Basic Res (µV)
	±5000	667	1333
	±2500	333	667
	±250	33.3	66.7
	±25	3.33	6.7
	±7.5	1	2
	±2.5	0.33	0.67
Accuracy ²	0 to +40°C ±(0.06% of setting + 0.8 mV)	-25 to +50°C ±(0.12% of setting + 0.8 mV)	-55 to +85°C (-XT only) ±(0.18% of setting + 0.8 mV)

Analogue Outputs

3 switched voltage, active only during measurement, one at a time

Ranges and Resolution	Voltage outputs programmable between ±2.5 V with 0.67 mV resolution		
Accuracy	0 to +40°C ±(0.06% of setting + 0.8 mV)	-25 to +50°C ±(0.12% of setting + 0.8 mV)	-55 to +85°C (-XT only) ±(0.18% of setting + 0.8 mV)

Resistance Measurements

Measurement types	4- and 6-wire full bridges, 2, 3 and 4 wire half bridges. Precise, dual polarity excitation using any of the 3 switched voltage excitations eliminates DC errors
Ratio Accuracy	±(0.04% of voltage reading + offset)/V _x

Pulse Counters

Maximum counts per scan	16.7 x 10 ⁶
Digital I/O Ports	4 ports software selectable, as binary inputs or control outputs

¹Range overhead of ~9% exists on all ranges to guarantee that full-scale values will not cause over-range. ²Resolution of DF measurements with input reversal. ³Basic resolution (Basic Res) is the A/D resolution of a single conversion. Resolution of DF measurements with input reversal is half the Basic Res.

Ordering Information

Datalogger Components

D1-1.1.2	CR1000 - Advanced datalogger and wiring panel, up to 14 multiplexers
D1-1.1.3	CR800 - Basic datalogger and wiring panel, up to 3 multiplexers
D1-1.2	Lead acid power supply, 115VAC / 220VAC, includes 12volt battery
D1-1.3	AWW100 - Vibrating Wire interface, for reading VW multiplexers or 1No VW instrument with thermistor
D1-1.4	AM16/32 - relay multiplexer, 16 channel with 4wire instruments, 32 channel with 2 wire instruments
D1-1.9	AWW4 - Vibrating Wire Interface, for reading VW multiplexers or 4No VW instrument with thermistor

Enclosures

D1-2.6	Enclosure, epoxy painted steel. H400mm x W400mm x D250mm
D1-1.6	Enclosure, epoxy painted steel. H600mm x W600mm x D250mm
D1-2.7	Enclosure, polyester/GRP. H530mm x W430mm x D200mm
D1-1.7	Enclosure, polyester/GRP. H745mm x W535mm x D300mm

Configuration and Wiring

D1-1.8	CR1000, Includes logger customer specified program and full testing
D1-2.8	CR800, Includes logger customer specified program and full testing
D1-1.4	Multiplexer, additional to a logger configuration

Direct Communication

D1-3.1	SC32B, RS232 opto isolated interface, for permanent use
D1-3.2	SC929, RS232 interface, for temporary use
D1-3.3	USB optically isolated interface cable

Telephone Modem

D1-3.4	TD32, telephone modem
--------	-----------------------

Digital Wireless Modem

D1-3.5	GSM digital transceiver
--------	-------------------------

Multidrop Interface

D1-3.9	Multidrop interface
D1-3.10	Power supply for interface at PC
CA-3.1-4-IC	4 core, Instrument cable, 7/0.20, screened

Weather Station

D1-4.1	Weather station Logger, CR10, SC32B, mains charger, battery backup, housed in 600mm x 400mm steel enclosure Components, temperature and relative humidity probe, anemometer, pyranometer and tipping bucket rain gauge
CA-3.1-4-IC	4 core, Instrument cable, 7/0.20, screened

Non-Mains Power Supply

D1-5.1	Solar panel, 10watt
D1-5.2	Solar shunt regulator
CA-3.1-4-IC	4 core, Instrument cable, 7/0.20, screened

Options & Accessories

D1-6.1	SC12 cable, connecting two peripherals to logger
D1-6.2	Desiccant to remove excess humidity
D1-6.5	Battery 12V 7Ah, additional battery for mains power dataloggers
D1-6.6	Lead acid battery 12V 16Ah, additional battery for non-mains battery powered dataloggers
D1-6.7	Desktop battery charger

soil
INSTRUMENTS



FM 611948

Bell Lane, Uckfield, East Sussex
TN22 1QL United Kingdom

t: +44 (0) 1825 765044 e: info@soilinstruments.com w: www.soilinstruments.com

Soil Instruments Limited. Registered in England. Number: 07960087. Registered Office: 3rd Floor, 1 Ashley Road, Altrincham, Cheshire, WA14 2DT