

TLT2 ELECTROLEVEL TILTSENSOR

Datasheet TLT2



Description

The Electrolevel Tiltensor is based on a proven Fredericks 0711 series electrolevel sensor and measures rotation of structures in the vertical plane.

The sensor is housed in a sealed enclosure incorporating an adjustable mounting plate.

The measurement of vertical rotation perpendicular to the structure is obtained by using an optional 90 degree angle bracket.

The sensor mounting incorporates an adjustment for zeroing and protects the sensor against thermal gradients.

Features

- Simple, well proven device, ideal for measuring tilt in structures
- Accurate and precise
- Measures vertical rotation

Benefits

- Easy to automate using data acquisition systems and 'Argus' software
- Removes the need for manual monitoring
- Compact
- Recoverable and reusable
- Suitable for safety critical applications
- Low power consumption



Comprehensive information about this product and our full range is available at www.soilinstruments.com
If you would like to speak with someone directly please call +44 (0)1825 765044 or email sales@soilinstruments.com

Operation

The Electrolevel Tiltensor consists of a precision glass electrolevel vial mounted in an inert ceramic compound which is itself placed in an adjustable mount.

The sensor is fixed to the structure. Once installed, thumbwheels at one end allow the sensor to be adjusted to the zero position using a handheld readout.

Associated products

For details on:

Catalogue code:

Datalogger	D1
HELM	TLT1-3
'Argus' Monitoring Software	D4

View our full product range on www.soilinstruments.com

Applications

The Electrolevel Tiltensor monitors vertical rotations of structures. Its most common use is to monitor settlement and heave of existing structures and tunnels caused by adjacent excavations or tunnelling works.

The sensor is especially useful where topographic measurements are precluded or where access is restricted.

Typical monitoring applications include:

- Brick and stone buildings
- Vertical rotation (heave and settlement) due to adjacent construction activities
- Bridges and dams
- Impounding and loading effects in short or long term
- Differential levels
- Tunnels
- Monitoring vertical rotation and track formation



THE TECHNICAL RATING FOR THIS PRODUCT:

As the correct installation of any monitoring sensor or system is vital to maximise performance and accuracy, Soil Instruments makes the following recommendations, for the skill level of the installation contractor.

ADDITIONAL SUPPORT

We offer installation and monitoring services to support this system. For more information please email : sales@soilinstruments.com or call : **+44 (0) 1825 765044**

ADVANCED



ADVANCED



The installer is trained and experienced in the installation of this type of instrument or systems, and is ideally a specialist Instrumentation and Monitoring contractor.

INTERMEDIATE



The installer already has previous experience and/or training in the installation of this instrument or system.

BASIC



As a minimum the installer has read and fully comprehends the manual, and if possible has observed these instruments or systems being installed by others.

Specifications

Sensor Type

	Electrolevel
Range	±45 arc minutes (±13mm/m)
Accuracy ¹	±0.1mm/m
Resolution ²	0.02% full scale
Repeatability	±0.05% full scale
Excitation voltage	2.5v AC
Current consumption	< 1µA
Output signal	Ratiometric AC
Operating temperature	-20 to +50°C
Zero adjustment range	±5° fine adjustment / ±25° coarse adjustment
Ingress protection	IP66

Cable Fitment

On site connection	Screw terminals
--------------------	-----------------

Dimensions

L 135mm x H 127mm x W 60mm

Weight

890g

¹ Accuracy within precision range (± 14 arc minutes)

² Resolution dependant on readout (CR1000)

Ordering Information

Electrolevel Tiltensor

Range $\pm 13\text{mm/metre}$ (± 45 arc minutes)

TLT2-1.5-1 Uniaxial tiltensor

Electrolevel Tiltensor Accessories

TLT2-1.5-3 90° bracket for TLT2-1.5-1. To read the rotation perpendicular to the structure for uniaxial tiltensors. Includes fixings

Connecting Cable and Fittings

CA-3.1-4-IC Instrument cable, 4 core, 7/0.20, screened

CA-3.2-4-FR Low smoke cable, 4 core, 16/0.20, screened

Handheld Electrolevel Levelling Tool - Helm

TLT1-3.1 Handheld electrolevel readout (HELM)

Manuals

MAN-173 Electrolevel beam, tilt and hand held electrolevel readout (HELM)

soil
INSTRUMENTS



FM 611948

Bell Lane, Uckfield, East Sussex
TN22 1QL United Kingdom

t: +44 (0) 1825 765044 e: info@soilinstruments.com w: www.soilinstruments.com

Soil Instruments Limited. Registered in England. Number: 07960087. Registered Office: 3rd Floor, 1 Ashley Road, Altrincham, Cheshire, WA14 2DT